

## Cordless Cap Lamp

Value series – for Petrochemicals, Surface Operations and Underground Hardrock Mines

### Features



Three operating modes – Standard Focus, High-Beam Focus, Spread



Thin design means Cap Lamp fits behind visor and allows it to go up and down



Lightweight, comfortable and ergonomic



Tough GERMAN enclosure material to withstand rough handling



World's safest and most reliable Panasonic battery



Made from Top Brand, high quality components and parts



Comes with free Angle Adjustable Bracket



### Product Specifications



#### IP Rating - IP67

Submersible in water up to 1m for 30min



#### Illumination

2800 Lx Standard Focus  
5500 Lx High-Beam Focus



#### Charging Time

7 h



#### Running Time

13 h Standard Focus



#### Ambient Temperature

-20~40 degrees



#### Weight

95 g



#### Certifications:

- Certificate #: IECEx TSA 19.0008
- Ex Marking: Ex ia op is IIB T3 Gb

#### Standard #:

- IEC 60079-0
- IEC 60079-11
- IEC 60079-28



Roobuck Pty Limited  
Suite 6, 20 West Street  
Brookvale, NSW 2100



+61 2 9938 1550



info@roobuck.com.au



roobuck.com.au

## CB8T Charging Bank For 8 Cordless Cap Lamps



### Features

- Portable, Wall Mountable, Vehicle Installation
- Lamp Charging Indicator
- Automatic over-load protection – cuts off that circuit when Cap Lamp battery is fully charged

### Specifications

Input	AC 90 – 265 V
Output	500 mA
Power Consumption	<150 W
Dimensions	33.4 x 18.2 x 6.6 cm
Weight	860 g

## CB28T Charging Bank For 28 Cordless Cap Lamps

### Features

- Wall Mountable
- Optional - Locking Bar
- Lamp Charging Indicator
- Automatic over-load protection – cuts off that circuit when Cap Lamp battery is fully charged
- Space to attach identification label

### Specifications

Input	AC 90-265 V
Output	500 mA
Power Consumption	<150 W
Dimensions	84 x 60 x 11.5 cm
Weight	9 kg



## Individual Chargers & Accessories

UCT: Single USB Charger

RCB: Angle Adjustable Bracket

